



## Ohaus Adventurer Series Balance, 2200 x 0.1 g

**Description:** Striking the ideal balance between inventive features and functional, uncomplicated weighing capabilities, the Ohaus AX2201/E incorporates all the applications necessary for routine weighing and measurement activities. With a color touchscreen, three level user management to fulfill GLP/GMP compliance capabilities, two USB ports, and much more, Adventurer is the most complete balance in its class.

### Features:

- Adventurer balances feature a color touchscreen, icon-based user interface, and an ergonomic design-making them easy to configure and use.
- The cloning feature allows you to save user and application settings to a USB flash drive which can be easily used to configure additional Adventurer balances.
- When using the minimum weight feature, the display clearly indicates that your current sample weight is below your defined minimum limit. This feature is set by the administrator.
- Durable construction, large weighing surfaces, and full housing in-use cover allow for use in lab, education and industrial environments.
- Adventurer's fast stabilization time improves productivity in the laboratory.
- The Adventurer is designed with various power-saving features that help reduce the environmental impact. These include auto-off and brightness controls.
- Easy to clean to ensure a safe workspace by minimizing contamination.
- 3 level user management function ensures data security and data traceability requirements.
- One administrator, two supervisors, and 10 users have preset accessibility in the software.
- Real-time clock function keeps accurate time even during power loss. GLP/GMP data output has the ability to record Sample name, Project names and Balance IDs to help meet traceability and compliance requirements.

USA | Canada | Australia | International

medisca.com

## Technical Specifications:

|  |                                       |
|--|---------------------------------------|
| <b>Model</b>                                 | AX2201/E                              |
| <b>Maximum capacity (g)</b>                  | 2,220.0                               |
| <b>Readability (g)</b>                       | 0.1                                   |
| <b>Repeatability, typical (g)</b>            | 0.1                                   |
| <b>Linearity (g)</b>                         | ±0.2                                  |
| <b>Stabilization time (sec)</b>              | 1.5                                   |
| <b>Power requirements</b>                    | AC Adapter (included)                 |
| <b>Data interface</b>                        | RS232-C<br>USB Device<br>USB Host     |
| <b>Calibration</b>                           | External                              |
| <b>Pan size: w x l (cm/in)</b>               | 19.5 x 17.5 / 7.7 x 6.9               |
| <b>Balance dimensions: w x l x h (cm/in)</b> | 35.4 x 23.0 x 10.0 / 13.9 x 9.1 x 3.9 |
| <b>Net weight (kg/lb)</b>                    | 4.6 / 10.2                            |

## Associated Products:

- 7363 – Ohaus Dot Matrix Printer SF40A, with Cable
- 8260 – Calibration Weight, 2 kg

**Warranty : 2 years**

**USA | CANADA | AUSTRALIA PACIFIC | EUROPE**

[WWW.MEDISCA.COM](http://WWW.MEDISCA.COM)

Please note that the information contained herein is for informational purposes only. The information is based on recognized compendia, manufacturers' instructions and/or other authoritative sources and texts. MEDISCA takes no responsibility for the validity or accuracy of this information. Customer MUST refer to USP, FDA, Health Canada, TGA and/or their State Board to ensure they comply with the specific regulations and ensure that appropriate procedures are in place.